

BRAKES

Disc Brakes - Escalade, Suburban, Tahoe, Yukon

SPECIFICATIONS

FASTENER SPECIFICATIONS

*FROM MY SER MANUAL FOR 2015-2017
COPY OF PAGE 3786 OF 13,754 PAGES!
ED SIEVERS DENVER CO*

Application	Specification	
	Metric	English
Brake Caliper Bleeder Screw - Front JD9	14 N.m	124 lb in
Brake Caliper Bleeder Screw - Front and Rear J95	10 N.m	89 lb in
Brake Caliper Bleeder Screw - Rear JD9	12 N.m	106 lb in
→ Brake Caliper Bracket Bolt - Front JD9	230 N.m	170 lb ft
→ Brake Caliper Bracket Bolt - Front and Rear J95	300 N.m	221 lb ft
→ Brake Caliper Bracket Bolt - Rear JD9	200 N.m	148 lb ft
→ Brake Caliper Guide Pin Bolt - Front JD9	100 N.m	74 lb ft
→ Brake Caliper Guide Pin Bolt - Front and Rear J95	105 N.m	77 lb ft
→ Brake Caliper Guide Pin Bolt - Rear JD9	52 N.m	38 lb ft
Brake Hose Fitting Bolt - Front and Rear JD9, J95	40 N.m	30 lb ft
Brake Rotor Bolt - Front JD9, J95	12 N.m	106 lb in
Rear Brake Shield Bolt - JD9	9 N.m	80 lb in
Rear Brake Shield Bolt - J95	10 N.m	89 lb in

DISC BRAKE COMPONENT SPECIFICATIONS

Application	Specification	
	Metric	English
Front Brakes - JB1, JD9		
• Rotor Discard Thickness*	28.0 mm	1.102 in
• Rotor Minimum Allowable Thickness After Refinish	28.5 mm	1.122 in

*NOTE: JD9 = 1500 SERIES
J95 = 2500 SERIES*